

KSS Flat Sheet Membrane Samples

Flat Sheet Membrane Samples for Feasibility Tests

MEMBRANE TYPE	
HR / HRX / RO	High Rejection RO membrane (99.6% NaCl Rejection)
SR3D / NF-200	NF membrane, 200 Dalton MWCO
SeIRO® MPF-34	Acid/Base Stable NF membrane, 200 Dalton MWCO
SeIRO MPF-36	Acid/Base Stable NF membrane, 1,000 Dalton MWCO
HFK-328 / 5K	Polyethersulfone UF membrane, 5K Dalton MWCO
HFK-131 / 10K	Polyethersulfone UF membrane, 10K Dalton MWCO
HpHT K328 / 5K	High pH, high temperature Polyethersulfone UF membrane, 5K Dalton MWCO
HpHT K131 / 10K	High pH, high temperature Polyethersulfone UF membrane, 10K Dalton MWCO
HFM-183	PVDF Positive charge UF membrane, 100K Dalton MWCO
MFK-618	Polyethersulfone MF membrane, 0.1 micron pore size
MFK-603 / MF-0.1	Polyethersulfone MF membrane, 0.1 micron pore size, high temperature operation

PRODUCT SPECIFICATIONS		
Model	Koch Part Number	Approximate Dimensions
HR / HRX / RO	8150001	40" x 18"
SR3D / NF-200	8150002	40" x 18"
SeIRO MPF-34	0770002	18" x 18"
SeIRO MPF-36	0770007	18" x 18"
HFK-328 / 5K	0030896	18" x 18"
HFK-131 / 10K	0030880	18" x 18"
HpHT K328 / 5K	0030841	18" x 18"
HpHT K131 / 10K	0030840	18" x 18"
HFM-183	0030889	18" x 18"
MFK-618	0030898	18" x 18"
MFK-603 / MF-0.1	0030893	18" x 18"

OPERATING AND DESIGN INFORMATION*		
Typical Operating Pressure	UF/MF:	30 - 120 psi (2.1 - 8.3 bar)
	NF/RO:	100 - 650 psi (6.8 - 44.8 bar)
Operating Temperature Range	NF/RO:	40 - 113°F (5 - 45°C)
	UF/MF:	40 - 130°F (5 - 55°C)
	UF HpHT:	40 - 140°F (5 - 60°C)
	MF:	40 - 176°F (5 - 80°C)

* Consult KSS Process Engineering for specific applications and other operating parameters

The information contained in this publication is believed to be accurate and reliable, but is not to be construed as implying any warranty or guarantee of performance. We assume no responsibility, obligation or liability for results obtained or damages incurred through the application of the information contained herein. Refer to Standard Terms and Conditions of Sale and Performance Warranty documentation for additional information

Koch Separation Solutions, Inc. 850 Main Street, Wilmington, MA 01887-3388
 Main: +1-978-694-7000 • Fax: +1-978-657-5208 • Toll Free: +1-888-677-5624

For complete contact information and listing of our global locations, visit www.kochseparation.com

©2022 Koch Separation Solutions, Inc. All rights reserved worldwide. For related trademark information, visit kochseparation.com/legal.